


ARDEX AF 545

Heavy Duty Epoxy Adhesive

ARDEX AF 545 is a two part easy to use water resistant and flexible epoxy adhesive. Engineered with high strength ARDEX AF 545 is suitable for heavy static rolling loads. **LOW VOC** 

LOCATION

- Permanent internal application

SUBSTRATES

- Hardboard underlay approved to AS 2458, Cementitious underlayment and concrete with moisture content that complies with AS 1884:2012

FLOOR COVERINGS

- Commercial homogeneous sheet vinyl
- Linoleum
- Rubber tile floor coverings (Contact ARDEX Technical Services)

COVERAGE

- On a primed smoothed substrate with 0.8 x 1.6 x 2.0mm U-notch trowel approximately 6m²/L of mixed adhesive

WORKING TIME

- Approximately 45–60 minutes

SET UP TIME

- Wet set – install immediately

PACKAGING

- Part A: 2L container with 2.5kg of adhesive
- Part B: 2L container with 2kg of adhesive

CODE

10426



ARDEX AF 545 QUICK FACTS

- Ultimate Bond Strength - Long term performance and reliability
- Water resistant - Suitable in wet operating conditions
- Heavy duty grab - Installs difficult coverings



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE