

ARDEX AF 748

Linoleum Adhesive

ARDEX AF 748 is a high performance wet set acrylic adhesive designed with strength to quickly lock linoleum to the substrate, including the difficult 'Roll Set' and manufacturing marks while minimising shrinkage and expansion. Additionally formulated to be a very forgiving adhesive that can be reactivated with heat during installation in small areas to ensure perfect installation. **LOW VOC** ★

LOCATION

- Internal permanent application

SUBSTRATES

- Hardboard underlay approved to AS 1859, cementitious underlay approved to AS 2908 and dry concrete with moisture content that complies with AS 1884:2012 or NZS AS 1884. Contact ARDEX Technical Services for other substrates including terrazzo, ceramic tiles and metal substrates

FLOOR COVERINGS

- Linoleum sheet
- Linoleum tiles with fibre glass backing

COVERAGE

- Using a 2.4mm V-Notch trowel approximately 3m²/L

WORKING TIME

- 25 minutes varying on substrate, temperature and humidity

SET UP TIME

- The linoleum is wet laid with 25 minutes adjustment time

PACKAGING

- 15 Litre pail containing 15kg of adhesive

CODE

12802



ARDEX AF 748 QUICK FACTS

- Solvent free – low VOC and user friendly
- Aggressive early grip – Reduce slippage and edge curl
- Long working time – easier more forgiving installation



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE