


ULTRA RAPID DRYING SELF-LEVELLING COMPOUND

ARDEX K55

Ultra Rapid Drying Self-Levelling Compound

ARDEX K 55 is a rapid drying levelling and smoothing compound designed to level and smooth internal subfloors prior to applying floor finishes. It is perfect for rapid renovation and repair work as most floor coverings can be installed after 1 hour.

LOW VOC 



LOCATION

- Internal in above or below grade applications

SUBSTRATES

- Concrete, Ceramic*, Terrazzo*, power-trowelled (burnished) concrete* and high strength concrete* greater than 35MPa
- *Please refer to the datasheet for more information

FLOOR COVERINGS

- Linoleum, vinyl, carpet
- Ceramic and quarry tiles
- Timber - parquetry and floating

COVERAGE

- 13m² at 1mm thick

THICKNESS

- 1mm to any depth
- Add 2-5mm aggregate for thicknesses over 10mm

DRYING TIME

- Walkable in 45-60 minutes
- Ready for floor coverings in 1-2 hours



ARDEX K55 QUICK FACTS

- Ultra rapid drying - ready to receive vinyl after 60 minutes
- Extended shelf life - 24 months when stored correctly
- Easy to install - 1mm to any thickness in one application
- Suitable for residential and commercial applications



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE