

# INDUSTRIAL LEVELLING COMPOUND

## ARDEX K80

### Rapid Drying Self-Levelling Topping

ARDEX K 80 is an Ardurapid levelling compound designed to provide a finished wear surface on new or old concrete substrates. The exceptional hardness is resistant to forklifts, trolleys and vehicles making ARDEX K 80 suitable in industrial, warehouses and garage applications.

LOW VOC



#### LOCATION

- Internal above or below grade applications

#### SUBSTRATES

- New and existing concrete and damp or moisture vulnerable concrete when used in conjunction with an ARDEX moisture control system

#### FLOOR COVERINGS

- Polyurethane coatings
- Epoxy coatings
- Specialty floor coatings

#### COVERAGE

- 2.4m<sup>2</sup> at 5mm

#### THICKNESS

- 5mm to 50mm

#### DRYING TIME

- Walkable in 2 hours
- Ready for coatings in 24 hours
- Trafficable in 48 hours



#### ARDEX K80 QUICK FACTS

- Ideal for creating wear surfaces for heavy duty applications
- Easy to install - 5mm to 50mm in one application
- Quick drying - walkable in 2 hours
- Superior flow - fast application
- Flexible - hand mix or pump application
- Suitable for residential, commercial and industrial applications



CONTACT US  
1300 788 780 | [www.ardexaustralia.com](http://www.ardexaustralia.com)



Download the Ardex app  
(search for 'ARDEX Australia')



**SYSTEMARDEX**  
PREMIUM PERFORMANCE