

ARDEX K 900 BF

Pumpable Bulkfill Levelling Compound

ARDEX K 900 BF is a cement based underlay for levelling subfloors prior to the application of a floor finish. Designed with a coarse sand aggregate and controlled flow for the easy and efficient installations of thick layers. It can also be used as a fast set screed when the water mixing ratio is reduced.

LOW VOC 

LOCATION

- Internal above grade applications
- Below grade application with ARDEX moisture barrier

SUBSTRATES

- New, existing or rough screeded concrete

FLOOR COVERINGS

- Linoleum, vinyl, carpet
- Ceramic and quarry tiles
- Timber floors (contact ARDEX Technical Services)

COVERAGE

- 1m² at 10mm, 2kg powder/mm/m²

THICKNESS

- 3–90mm thick

DRYING TIME

- Walkable from 4 hours
- Overlay with ARDEX smoothing compounds from 16 hours

PACKAGING

- 20kg triple layered bag

CODE

24954



ARDEX K 900 BF QUICK FACTS

- Economical – Ideal for levelling up to 90mm
- Easy to install – Engineered for controlled flow
- Strong – Suitable for heavy duty traffic
- Low Odour



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE