

CRACK INJECTION

ARDEX RA 54

Fast Setting Semi-Rigid Polyurea Joint Sealant

ARDEX RA 54 is used to fill interior control joints or new construction saw joints on horizontal concrete surfaces. Designed for industrial floor applications receiving heavy duty vehicle traffic. Can be used in exterior applications, when minimal (10% to 12%) joint movement from thermal cycling will occur. With a very rapid cure time, repaired joints can be opened to traffic in 90 minutes.

LOCATION

Designed for industrial floor applications receiving heavy duty vehicle traffic. This can be used in exterior applications, when minimal (10% to 12%) joint movement from thermal cycling will occur.

SUBSTRATES

Concrete

COVERAGE

Approx. 3 linear metres with a joint size of 3 x 25mm.

COLOURS

Grey

DRYING AND CURING

Can be shaved in approx. 45 minutes, open to full traffic in 90 minutes.

VOC CONTENT

0g/L

PACKAGING

245mL cartridge



ARDEX RA 54 QUICK FACTS

- Fill interior control joints or new construction joints
- Heavy duty vehicle traffic
- Designed for industrial floor applications
- Rapid cure - Trafficable in 90 minutes



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE