

ARDEX S 4

Green Slab Seal

ARDEX S 4 is a water based liquid solution designed to penetrate deeply into the concrete slab reducing the risk of moisture related problems. ARDEX S 4 can be applied to green concrete slabs where it will penetrate deeply into the slab and react with the free lime forming a hardened gel substance; filling pores, voids, hairline cracks and trapped air cells, creating a permanent slab seal against moisture. **LOW VOC** ★

INSTALLATION

- ARDEX S 4 is applied using a backpack low pressure sprayer for small to medium jobs
- 60m² at a coverage rate of 4m² per litre

AFTER INSTALLATION

- It is important that the treated surface is sanded and vacuumed after 24 hours from application
- Refer to the product data sheet, or contact ARDEX technical services

SUBSTRATES

- New or green existing concrete slabs

COVERAGE

- ARDEX S 4 will cover approximately 60m²/15L cube at a coverage rate of 4m²/L

PACKAGING

- 15L cube

CODE

13428



ARDEX S 4 QUICK FACTS

- Permanent moisture block for internal concrete subfloors
- Used as a concrete curing agent at time of pour
- Easy application using low pressure backpack sprayer



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE