

ARDEX WPM 150

(Shelterbit 3/160 Membrane)

ARDEX WPM 150 (Shelterbit 3/160) is an A.P.P. (Atactic Polypropylene) Plastomeric type modified bitumen membrane, consisting of a specially formulated bituminous compound of distilled asphalt modified with selected high grade visco-elastic polymers and reinforced with a polyester reinforcement.

TYPICAL USES

ARDEX WPM 150 is used as a single layer or multi-layer tanking membrane in horizontal or vertical applications, also for waterproofing balconies, terraces and roofs. ARDEX WPM 150 membrane is a sandwich membrane and must be protected from UV radiation.

TYPE

APP

REINFORCEMENT

Fibreglass and Polyester (150g/m²)

THICKNESS/ WEIGHT

3.0mm

TOP SURFACE

Sand

BOTTOM SURFACE

Torch film

HEAT STABILITY

110°C

ROLL SIZE

1 x 10m

ROLL WEIGHT

35kg

ROLLS PER PALLET

28



ARDEX WPM 150 QUICK FACTS

- 3.0mm combined reinforced APP bitumen membrane
- Excellent elongation
- Cold flexibility to -5°C



CONTACT US
1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEMARDEX
PREMIUM PERFORMANCE