

# RENDERS AND SCREEDS

## ARDEX WR 100

### General Purpose Acrylic Render

ARDEX WR 100 is a fine-grade acrylic render suitable for rendering walls, both internally and externally, at an application thickness from 2-10 mm.

#### LOCATION

Internal/External

#### SUBSTRATES

Masonry (brickwork & blockwork), concrete walls, AAC – autoclaved aerated concrete blocks and panels, EPS foam panels.

#### THICKNESS

2-10mm

#### BENEFITS

No maturing time required; can be applied immediately after mixing.

#### COVERAGE

Coverage will vary depending on the condition of the surface and site conditions. As a guide, 20kg of ARDEX WR 100 mixes to 13 litres of mortar. As a guide, 20kg will cover:

- 6.5m<sup>2</sup> at 2mm thickness
- 2.6m<sup>2</sup> at 5mm thickness
- 1.3m<sup>2</sup> at 10mm thickness

#### COLOURS


Light grey powder

#### DRYING TIMES

Touch-dry in 1–2 hours, subsequent coats after 4–8 hours.

#### PACKAGING

20kg bag



#### ARDEX WR 100 QUICK FACTS

- Easy to use with superior non-slump and creamy consistency
- Produces a build-up from 2-10mm with a fine finish, with no sag-ging or cracking
- No maturing time required



CONTACT US  
1300 788 780 | [www.ardexaustralia.com](http://www.ardexaustralia.com)

