



ARDEX CA 750 Adhesive

Contact Adhesive for Vinyl Skirting and ARDEX WeldTec Membranes

Water-based

Environmentally friendly

Low VOC content - meets Green Building Council of Australia Green Star IEQ-13 requirements

Can be used with ARDEX *SpeedTec* Catalyst spray

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Phone: 1300 788 780
Email: technicalservices@ardexaustralia.com
www.ardexaustralia.com

ARDEX New Zealand Ltd
15 Alfred Street
Onehunga, Auckland, 1061
Phone: 0800 227 339
Email: info@ardexnz.com
www.ardex.co.nz

ARDEX CA 750 Adhesive

Contact Adhesive for Vinyl Skirting and ARDEX WeldTec Membranes

DESCRIPTION

ARDEX CA 750 is a ready-to-use water-based contact adhesive for bonding both vinyl skirting and ARDEX WeldTec Membranes such as WPM 750 or WPM 1000.

ARDEX SpeedTec® Catalyst can be used to improve the initial grab of ARDEX CA 750 Adhesive.

TO (SUBSTRATES)

Porous concrete, cement render, unsealed fibre-cement sheet and plasterboard.

SUBSTRATE PREPARATION

The surface being adhered to must be smooth, clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and other barrier materials. Ensure surfaces are dry before waterproofing, with no residual or permanent damp. Every effort shall be made to ensure substrates that receive membranes bonded with ARDEX CA 750 Adhesive are sufficiently dry. Substrates prone to high moisture content (concrete, brick, concrete block, stone, etc.) shall be subjected to a moisture test prior to application.

VINYL SKIRTING FIXING TECHNIQUE

With a brush or roller apply ARDEX CA 750 Adhesive to both the underside of the skirting and the substrate at a rate of 5m²/litre, to allow approximately the same drying time. When the bonding adhesive is ready generally 30 minutes to 4 hours (the colour of the adhesive will be clear not white) apply the skirting to the substrate and firmly apply pressure. ARDEX SpeedTec® Catalyst can be used for skirting applications and can be lightly misted over the adhesive to increase the speed of application and grab to the substrate.

Important Note: Take care not to overspray the Catalyst to any metal or other surfaces. Better results are obtained with dry bond, ie. both sides of ARDEX CA 750 application is dry.

WeldTec MEMBRANE (UNDERTILE BUTYNOL) FIXING TECHNIQUE

With a brush or roller apply ARDEX CA 750 Adhesive to both the underside sheet and the substrate at a rate of 10m²/litre, to allow approximately the same drying time. It is recommended to use ARDEX SpeedTec® Catalyst. Apply a light mist to over adhesive and quickly bond the membrane to the substrate. When the bonding adhesive is ready to be mated (the colour of the adhesive will be clear not white) start at the fold and roll the previously coated portion of the sheet into the coated substrate slowly and evenly to avoid wrinkles. To ensure proper adhesion, compress the bonded portion of the sheet to the substrate with a pressure roller.

Important Note: Take care not to apply bonding adhesive over an area that will later be spliced or seamed to another sheet or flashing.

DRYING TIME

Allow the bonding adhesive to flash off until clear. Touch the bonding adhesive surface with a clean, dry finger and push forward to be certain the adhesive does not stick or string and to ensure that the adhesive is ready throughout its thickness. If either motion exposes wet or stringy adhesive when the finger is lifted, then it is not ready for bedding. ARDEX CA 750 Adhesive will change from white to colourless as the water evaporates indicating mating readiness. Flash-off times will vary depending on substrate temperatures and ambient air conditions.

Without ARDEX SpeedTec® Catalyst open time is from not less than 30 minutes and not more than 4 hours. To achieve instant grab or mating of substrates spray ARDEX SpeedTec® Catalyst onto freshly applied ARDEX CA 750 Adhesive. ARDEX SpeedTec® Catalyst is not compatible with any metal surfaces, it must not be used where metal is present and overspray must be considered when applying.

PACKAGING

ARDEX CA 750 Adhesive is available in 4L and 15L pails.

COVERAGE

1L of ARDEX CA 750 Adhesive is sufficient for approximately 5m² (both sides) and should be applied using a brush or roller. The coverage will vary depending on substrate condition and application technique.

CLEAN UP

Wash brushes and equipment in cold water then mineral turps for final clean, store in water between multiple applications.

SHELF LIFE

ARDEX CA 750 Adhesive has a shelf life of 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity. Do not store below 5°C.

SAFETY DATA

Avoid contact with skin and eyes; in case of contact with the eyes, wash out immediately with fresh running water. If irritation continues, seek medical attention. Wear protective gloves, clothing and eye protection. Avoid inhaling dust/fume/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.ardexaustralia.com

TECHNICAL DATA

Colour: Off-White paste

Application Properties at 23°C and 50% RH

Shear Bond Strength, AS 3553:

24 hours > 0.5MPa

7 days > 0.5 MPa

Heat ageing > 0.5 MPa

GUARANTEE

ARDEX Australia Pty Ltd ("we" or "us") guarantees this product ("our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of purchase. Our liability under this guarantee is limited to our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or compensation, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow published instructions or any act or circumstance beyond our control, including shade variations and efflorescence. If you wish to make a claim under this guarantee you must notify us (ARDEX Australia Pty Ltd, 20 Powers Road Seven Hills NSW 2147; Toll Free: 1800 224 070; Email: techinfo@ardexaustralia.com) and provide evidence of your purchase of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2020.

All aforementioned products are the trademarks of ARDEX Australia Pty Ltd, its licensors and affiliates.

This datasheet was issued in February 2020 and is valid for 3 years, in some instances a newer version may be published. Always refer to www.ardexaustralia.com for the latest technical data from ARDEX Australia Pty Ltd.