



ABAPRIME

Wall and Floor Single Part Primer

- **Pink**
- **Internal & External**
- **Australian Made**

DESCRIPTION

ABA Abaprime Single Part Primer is a water-based primer used for improving the adhesion of ABA and ARDEX products to smooth, dense and various non porous substrates. It is easy to apply with a brush or roller with applications of subsequent products able to take place with minimal downtime.

ABA Abaprime Single Part Primer is suitable for internal and external wall or floor applications.

FOR USE WITH

ABA Abaprime Single Part Primer is compatible with subsequent applications of ABA tile adhesives, floor levelling compounds and in non fully immersed conditions with ABA undertile waterproofing membranes.

TO (SUBSTRATES) FOR TILE ADHESIVES

- Internal particleboard, plywood, sheet timber
- Medium density fibre-cement sheet, compressed fibre-cement sheet
- Jointing compound over plasterboard
- Concrete, renders, screeds
- Masonry and lightweight concrete blocks
- Autoclaved aerated concrete (AAC)
- Existing surface prepared glazed tiles (not suitable for shower floors or permanently immersed conditions).

Contact ARDEX Technical Services for specifics with:

- Metal surfaces
- Plastics
- Painted surfaces
- Existing vinyl
- Epoxy coatings

TO (SUBSTRATES) FOR FLOOR LEVELLERS

- Internal particleboard, plywood, sheet timber ARDITEX NA only
- Compressed fibre cement sheets
- Concrete, masonry and lightweight concrete blocks
- Autoclave aerated concrete (AAC)
- Existing glazed tiles (tiles to be de-glazed before priming)

Note: Not suitable for steel trowelled finish concrete where floor leveller is being applied.

SUBSTRATE PREPARATION

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and old surface coatings.

Ensure surfaces are dry prior to application, with no residue or permanent dampness.

Surfaces must be suitable for the application of the subsequent product being used.

APPLICATION

Stir product before use.

On floors, spread the material using a brush or long nap roller to cover at a rate of at least 6-10m² per litre over the entire surface to be primed.

For floor levelling topping application is highly absorbent substrates dilute ABA Abaprime Single Part Primer with water 1:1 by volume.

All tools should be cleaned with water immediately after use.

DRYING TIME

Ensure the ABA Abaprime Single Part Primer is fully dry prior to the application of subsequent products, allow approximately 20 minutes at 23°C and 50% relative humidity.

Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.

COVERAGE

One litre of ABA Abaprime Single Part Primer is sufficient for 6 - 10m², therefore the approximate coverage on each of the following units is: 1L per 6 - 10m² coverage will vary depending on the porosity of the surface and method of application.

PACKAGING

ABA Abaprime Single Part Primer is packed in plastic pails - net volume 1L and 4L

SHELF LIFE

ABA Abaprime Single Part Primer has a shelf life of 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

Store away from direct sunlight. Replace lid tightly after use.

Pay attention to the following:

Do not empty excess primer back into the original packaging as this may cause contamination of the contents.

Do not use in negative hydrostatic pressure situations.

Do not apply below 5°C or above 35°C.

SAFETY DATA

Avoid contact with skin and eyes; in case of contact with the eyes, wash out immediately with fresh running water. If irritation continues, seek medical attention. Wear protective gloves, clothing and eye protection. Avoid inhaling dust/ fume/ gas/ mist/ vapours/ spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents, dispose of packaging thoughtfully and recycle where possible. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.abaaustralia.com.au



TECHNICAL DATA

Appearance:	Pink Liquid
Coverage:	Approx 6 - 10m ² /litre
Drying Time:	Approx 20 minutes (at 23°C and 50% relative humidity)

PRODUCT GUARANTEE



Ardex Australia Pty Ltd (“we” or “us”) guarantees this product (also referred to as “our goods”) is free from manufacturing defects and will perform to any applicable specification published by us for 15 years from the date of application of the product if such application occurs within this product’s specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (address: 7/20 Powers Road Seven Hills NSW 2147; phone: 1800224070; email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a “consumer” under the Australian Consumer Law and to that extent you need to be aware that: “Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure”.

ARDEX AUSTRALIA PTY LTD

**ABA Products manufactured by
ARDEX Australia Pty Ltd**

20 Powers Road Seven Hills NSW 2147
technicalservice@ardexaustralia.com
www.abaustralia.com.au

ABA Technical Services Toll Free: 1800 300 863

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them. This datasheet was issued in October 2019 and is valid for 3 years, in some instances a newer version may be published. Always refer to www.abaustralia.com.au for the latest technical data. © ARDEX Australia Pty Ltd 2019. All aforementioned products are the trademarks of ARDEX Australia Pty Ltd, its licensors and affiliates.