TROCADERO – @ HAMER HALL

Victoria, Australia

INSTALLER:

Concrete Resurfacing Systems www.polishedconcretemelbourne.com.au/

BUILDER:

Liquid Lines www.liquidlines.com.au

ARCHITECT:

Allan Powell Architects www.allanpowell.com.au


PANDOMO SYSTEM:

Pandomo TerrazzoMicro

PROJECT ADDRESS:

Under Hamer Hall, Southbank

The right mix



The acoustic requirements of the project meant that pouring and grinding a concrete slab was not feasible, as the 70mm thickness did not meet the requirements. Pandomo can be installed at 11mm thickness, or on an unbonded screed of 45mm thickness to provide a thinner and efficient solution to traditional terrazzo flooring.

Pandomo – Producing a continually clean floor

Being a bar and food serving area, stain resistance was critical in ensuring that the floor remained stain resistant.

Concrete Resurfacing Systems worked with Liquid Lines to ensure the most suitable sealer

was employed to provide piece of mind in the area of stair resistance. Ardex can work with you on your project to ensure that the most suitable sealer is specified relating to your flooring performance requirements.

Pandomo - Goes with the flow

As the project required large pieces of black granite to be embedded in the flooring, the Pandomo TerrazzoMicro's ability to self- level and flow, meant the finish was able to be easily installed around the large pieces of black granite, which was adhered to the floor.

Additional Information Online

TerrazzoMicro



www.ardex-pandomo.com





DOMO